

**Floorstanding cistern Universal for floorstanding WC pan
82866.1**



TECHNICAL DATA

Order no.	82866.1
Certified to	EN 14055
matching for	Floorstanding WC pan rimless, order no. 82333.6
Specification	floorstanding Flushing mechanism Dual-Flush water condensation insulation Charge 881 – 6/3-l (5/3-l-flush, 4,5/3-l-flush)
Water inlet	concealed top left rear, 1/2" brass
Weight	21,5 kg
Mounting acc. incl.	Fastening kit Angle valve for rear water inlet Water inlet hose
Mounting acc. excl.	for VARIO-outlet 70 - 220 mm LAUFEN-

connection, order no. 89009.2 for VARIO-outlet 220 - 305 mm only LAUFEN- connection, order no. 89902.5
Colours see colour table

SPECIFICATION TEXT

Floorstanding cistern Universal KARTELL BY LAUFEN, sanitary ceramic EN 14055
 dimensions 400/410 x 140 x 980 mm
 Dual-Flush 6/3-l (5/3-l-flush, 4,5/3-l-flush)
 concealed water inlet top left rear, 1/2" brass
 matching floorstanding WC pan rimless, order no. 82333.6
 Special feature: water condensation insulation
 Order no. 82866.1

TECHNICAL DRAWINGS / S 1 : 20

