

Technical Datasheet SW 12 H

- Primarily for cleaning jobs in workshops and industrial production
- Drain on the back, to be operated on the side



Elektrical Data:

- Mains voltage / Variants: 100-120 / 220-240 (Vac)
- Ultrasonic Frequency: 37 kHz
- Power consumption total: 1000 Watt
- Ultrasonic power effective: 200 Watt
- Ultrasonic peak max.: 800 Watt
- Heating power: 800 Watt
- Temperature range: 30°C to 80°C in 5°C steps
- Ultrasonic Intensity (W / cm²): 2,6
- Timer: 1 till 30 min. and ∞
- Temperature range: 30°C – 80°C variable in 5°C steps

Mechanical Data:

- Tank max volume (approx. litre): 12.75
- Tank service volume (approx. litre): 9.00
- Tank internal dimensions: 297 x 238 x 200 (W x D x H / approx. mm)
- Unit external dimension: 380 x 272 x 323 (W x D x H / approx. mm)
- Weight (approx. Kg): 7.5
- Material Housing (Stainless steel): V2A 1.4301 (AISI 304)
- Material Tank (Stainless steel): V2A 1.4301 (AISI 304)
- Thickness Tank (approx. mm): 0.8

Technical properties:

- Number of transducer: 4
- Unit handles: 2
- Drain Diameter (inch“): 3/8“

Accessories:

- Basket internal dimensions (approx. mm): 240 x 181 x 120
- Basket loading (approx. Kg): 7.0
- Basket (order-no.): 100 402
- Cover: 100 004