

ПЕЧИ РОТАЦИОННЫЕ

СЕРИЯ G



Компактные размеры, надежная структура, улучшенная конструкция и широкая функциональность одновременно. Ротационные печи Apach Bakery Line серии G были специально проверены на тяжелые непрерывные циклы выпечки и предназначены как для небольших и ремесленных, так и для промышленных пекарен.

СТАНДАРТНОЕ ОБОРУДОВАНИЕ

- ◆ Версия TS: многофазная панель TOUCH SCREEN с 7 дюймовым TFT, 99 программ с изображениями товаров и USB портом, автоматически программируемый клапан
- ◆ Версия DP: цифровая панель управления с 30 сохраняемыми программами, ЖК-экраном и светодиодным дисплеем, программируемая система зажигания, двухскоростной вентилятор
- ◆ Версия EMP: электромеханическая панель управления
- ◆ Вращение с помощью крюка
- ◆ Пониженная скорость обдува для деликатной продукции
- ◆ Защита уплотнителей для лучшей теплоизоляции и более длительного срока службы
- ◆ Козырек с вытяжкой пара
- ◆ Дверь из нержавеющей стали с двойным остеклением и системой открывания на 180°
- ◆ Клапан предельного давления в камере
- ◆ Облегченная система закрытия дверей, не требующая значительных физических усилий
- ◆ Высокопроизводительный парогенератор с коротким временем восстановления
- ◆ Доступ к горелке или ТЭНам с левой стороны
- ◆ Доступна в электрической или газовой версии (для газовой, LPG или газовой/дизельной горелки)
- ◆ Ручка двери выполнена из стали с пониженной теплопроводимостью; внутренняя ручка для безопасности
- ◆ Высококачественная термоизоляция за счет использования панелей из высокоплотной минеральной ваты
- ◆ Внутренние углы в камере закруглены для легкости и безопасности очистки
- ◆ Камера печи, козырек и фронтальная отделка полностью из нержавеющей стали

ОПЦИИ / АКСЕССУАРЫ

- ◆ Возможность установки печей в линию (доступ для обслуживания сзади)
- ◆ Платформа (только для G68)
- ◆ Автоматический подъем крюка (только для G68)
- ◆ Доступ к горелке или ТЭНам с правой стороны
- ◆ Усиленные ТЭНы для электрических печей для интенсивного использования
- ◆ Панель на козырьке, показывающая время до конца цикла и температуру в камере

ПРЕИМУЩЕСТВА

- ◆ Надежная структура
- ◆ Улучшенная конструкция и функциональность
- ◆ Оптимальное энергопотребление
- ◆ Полный набор опций, необходимых для выпечки любого типа продукта
- ◆ Современный и технологичный дизайн

КОМПЛЕКТАЦИЯ			
EMP	DP	TS	
✗	✗	✓	Многофазная панель touch screen с 7 дюймовым TFT, 99 программ с изображениями товаров и USB - портом, автоматически программируемый клапан
✗	✓	✗	Цифровая панель управления с ЖК-экраном и светодиодным дисплеем, 30 сохраняемых программ
✓	✗	✗	Электромеханическая панель управления
✓	✓	✓	Пониженная скорость для деликатных продуктов
✓	✓	✓	Система вращения при помощи крюка
✓	✓	✓	Козырек с вытяжкой пара
✓	✓	✓	Дверь с двойным остеклением с открытием на 180°
✓	✓	✓	Теплоизоляция наружных панелей из нержавеющей стали с использованием панелей из высокоплотной минеральной ваты
✓	✓	✓	Внешние панели из нержавеющей стали
✓	✓	✓	Запатентованный парогенератор для массивного производства пара с минимальным временем восстановления
✗	✓	✓	Автоматическая заслонка пароудаления
✓	✗	✗	Ручная заслонка пароудаления
✓	✓	✓	Внешний электрошкаф (размещается сзади, сверху или на стене)
✓	✓	✓	Печь поставляется в разобранном виде (по запросу в 2 или 3 модулях или в полной сборке)
✓ По умолчанию ✗ Опция			

МОДЕЛЬНЫЙ РЯД СЕРИИ G (РАЗМЕР ЛИСТОВ 40X60) ЭЛЕКТРИЧЕСКИЕ									
Модель	Версия	Панель управления	Тип сборки	Габариты			Вес кг	Мощность кВт	Среднее потребление кВт/ч
				д	ш	в			
				мм	мм	мм			
G46E TS	Премиум	Touch screen	Полный разбор	1000	1420	2340	650	24+1,5	18
G46E TS2M		Touch screen	2 модуля						
G46E TSTA		Touch screen	Полная сборка						
G46E DP		Цифровая	Полный разбор						
G46E DP2M		Цифровая	2 модуля						
G46E DPTA		Цифровая	Полная сборка						
G46E EMP	Базовая	Электромеханическая	Полный разбор						
G46E EMPTA		Электромеханическая	Полная сборка						

**МОДЕЛЬНЫЙ РЯД СЕРИИ G (РАЗМЕР ЛИСТОВ 40X60)
ГАЗОВЫЕ**

Модель	Версия	Панель управления	Тип сборки	Габариты			Вес	Мощность	Среднее потребление
				д	ш	в			
				мм	мм	мм			
G46C TS	Премиум	Touch screen	Полный разбор	1000	1420	2340	700	40000	25000
G46C TS2M		Touch screen	2 модуля						
G46C TSTA		Touch screen	Полная сборка						
G46C DP		Цифровая	Полный разбор						
G46C DP2M		Цифровая	2 модуля						
G46C DPTA		Цифровая	Полная сборка						
G46C EMP	Базовая	Электромеханическая	Полный разбор	1000	1420	2340	700	40000	25000
G46C EMPТА		Электромеханическая	Полная сборка						

**МОДЕЛЬНЫЙ РЯД СЕРИИ G (РАЗМЕР ЛИСТОВ 60X80)
ЭЛЕКТРИЧЕСКИЕ**

Модель	Версия	Панель управления	Тип сборки	Габариты			Вес	Мощность	Среднее потребление
				д	ш	в			
				мм	мм	мм			
G68E TS КРЮК	Премиум	Touch screen	Полный разбор	1430	1970	2540	1200	49+2,3	36
G68E TST ПЛАТФОРМА		Touch screen					1272		
G68E DP КРЮК		Цифровая					1200		
G68E DPT ПЛАТФОРМА		Цифровая					1272		
G68E EMP КРЮК	Базовая	Электромеханическая	Полный разбор	1430	1970	2540	1200	49+2,3	36
G68E EMPТ ПЛАТФОРМА		Электромеханическая					1272		

**МОДЕЛЬНЫЙ РЯД СЕРИИ G (РАЗМЕР ЛИСТОВ 60X80)
ГАЗОВЫЕ**

Модель	Версия	Панель управления	Тип сборки	Габариты			Вес	Мощность	Среднее потребление
				д	ш	в			
				мм	мм	мм			
G68C TS КРЮК	Премиум	Touch screen	Полный разбор	1430	1970	2540	1255	40000	25000
G68C TST ПЛАТФОРМА		Touch screen					1327		
G68C DP КРЮК		Цифровая					1255		
G68C DPT ПЛАТФОРМА		Цифровая					1327		
G68C EMP КРЮК	Базовая	Электромеханическая	Полный разбор	1430	1970	2540	1255	40000	25000
G68C EMPТ ПЛАТФОРМА		Электромеханическая					1327		

ROTARY RACK OVENS

G SERIES



Compact dimensions, solid structure, refined design and great functionality at the same time. Apach Bakery Line G series rotary ovens are highly reliable products that offer wide warranties of quality to the most exigent users.

STANDARD EQUIPMENT

- ◆ TS version: TOUCH SCREEN control panel with 7" TFT, 99 multiphase programs with products' images, programmable steam damper
- ◆ DP version: digital control panel with new generation multifunction-rotary switch for quick selection of the different controls, LCD screen, 30 storable programs, 2-speed baking ventilation
- ◆ EMP version: : electromechanical control panel
- ◆ Hook turning system geared by motor-reducer with safety clutch
- ◆ 2-speed baking ventilation (ideal for delicate pastry or soft bread)
- ◆ Impact-free protected silicon joints mounted on the door
- ◆ Hood with extractor
- ◆ Stainless steel double glazed "TOTAL VISION" door equipped with 180° opening system
- ◆ Powerful steam generator designed and tested for massive steam production with very fast recovery times
- ◆ Highly refractory combustion chamber that can be totally inspected, with excellent performances, covered by a 3-years warranty
- ◆ Fast-recovering powerful steam generator
- ◆ Access to the burner or resistances from the left side
- ◆ Available in electric or fired version (for gas, LPG or gasoil/diesel burner)
- ◆ Rear heat exchanger including stainless steel highly-refractory firebox with left-side access for maintenance
- ◆ Heavy duty insulation with pre-compressed rockwool panels
- ◆ Practical upper rotation hook allowing the rack's movement and the oven's cleaning
- ◆ Stainless steel interior/exterior

OPTIONS / ACCESSORIES

- ◆ Turntable (except G46 range)
- ◆ Automatic rack lifter (except G46 range)
- ◆ Access to the burner or resistances from the right side
- ◆ Extra powered heating elements for electric ovens - intensive use or frozen bread
- ◆ Display on the hood showing baking time/chamber temperature

ADVANTAGES

- ◆ Solid structure
- ◆ Refined design and functional
- ◆ Optimal energy consumption
- ◆ A complete set of options required for any type of product
- ◆ Modern and technological design

EQUIPMENT			
EMP	DP	TS	
✘	✘	✓	TOUCH SCREEN control panel with 7" TFT, 99 multiphase programs with products' images, programmable steam damper
✘	✓	✘	Digital control panel with new generation multifunction-rotary swith for quick selection of different controls, LCD screen, 30 storable programs
✓	✘	✘	Electromechanical control panel
✓	✓	✓	2-speed baking ventilation (ideal for delicate pastry or soft bread)
✓	✓	✓	Hook turning system geared by motor-reducer with safety clutch
✓	✓	✓	Hood equipped with extractor
✓	✓	✓	Stainless steel double glazed door equipped with 180° opening system
✓	✓	✓	Heavy duty insulation with pre-compressed rockwool panels
✓	✓	✓	Stainless steel interior/exterior
✓	✓	✓	Powerful steam generator (protected by a patent), designed and tested for massive steam production with very short recovery times
✘	✓	✓	Automatic damper for steam removal
✓	✘	✘	Manual damper for steam removal
✓	✓	✓	External electrical cabinet (positioned at the back, top or wall)
✓	✓	✓	The oven is delivered disassembled (on request in 2 or 3 modules or fully assembled)
✓ Default ✘ Option			

THE LINEUP G SERIES (TRAYS 40X60) ELECTRIC									
Model	Version	Control panel	Assembly	Dimensions			Weight	Power	Average consumption
				L	W	H			
				mm	mm	mm	kg	kW	kW/h
G46E TS	Premium	Touch screen	Unassembled	1000	1420	2340	650	24+1,5	18
G46E TS2M		Touch screen	2 modules						
G46E TSTA		Touch screen	Total assembled						
G46E DP		Digital	Unassembled						
G46E DP2M		Digital	2 modules						
G46E DPTA		Digital	Total assembled						
G46E EMP	Basic	Electromechanical	Unassembled	1000	1420	2340	650	24+1,5	18
G46E EMPTA		Electromechanical	Total assembled						

THE LINEUP G SERIES (TRAYS 40X60) BURNER									
Model	Version	Control panel	Assembly	Dimensions			Weight	Power	Average consumption
				L	W	H			
				mm	mm	mm	kg	Kcal/h	Kcal/h
G46C TS	Premium	Touch screen	Unassembled	1000	1420	2340	700	40000	25000
G46C TS2M		Touch screen	2 modules						
G46C TSTA		Touch screen	Total assembled						
G46C DP		Digital	Unassembled						
G46C DP2M		Digital	2 modules						
G46C DPTA		Digital	Total assembled						
G46C EMP	Basic	Electromechanical	Unassembled	1000	1420	2340	700	40000	25000
G46C EMPTA		Electromechanical	Total assembled						

THE LINEUP G SERIES (TRAYS 60X80) ELECTRIC									
Model	Version	Control panel	Assembly	Dimensions			Weight	Power	Average consumption
				L	W	H			
				mm	mm	mm	kg	kW	kW/h
G68E TS HOOK	Premium	Touch screen	Unassembled	1430	1970	2540	1200	49+2,3	36
G68E TST TURNTABLE		Touch screen					1272		
G68E DP HOOK		Digital					1200		
G68E DPT TURNTABLE		Digital					1272		
G68E EMP HOOK	Basic	Electromechanical	Unassembled	1430	1970	2540	1200	49+2,3	36
G68E EMPT TURNTABLE		Electromechanical					1272		

THE LINEUP G SERIES (TRAYS 60X80) BURNER									
Model	Version	Control panel	Assembly	Dimensions			Weight	Power	Average consumption
				L	W	H			
				mm	mm	mm	kg	Kcal/h	Kcal/h
G68C TS HOOK	Premium	Touch screen	Unassembled	1430	1970	2540	1255	40000	25000
G68C TST TURNTABLE		Touch screen					1327		
G68E DP HOOK		Digital					1255		
G68E DPT TURNTABLE		Digital					1327		
G68E EMP HOOK	Basic	Electromechanical	Unassembled	1430	1970	2540	1255	40000	25000
G68E EMPT TURNTABLE		Electromechanical					1327		