


A: Please follow the instructions, properly install and place the equipment, connect the water supply pipe, drain pipe, and reserve additional space 10cm at the installation site to meet the installation requirements. (Air cooling equipment needs more space to meet the air flow and heat discharge.)
 B: The cooling effect depends on the heat dissipation environment, please keep ventilation
 C: Optional 6/10/15cm adjustable legs.

A: 请按照说明书, 正确安装。摆放设备供水、排水管、在安装现场预留10厘米额外空间, 以满足安装要求 (风冷设备, 需要更多的空间, 以满足空气流通和热量排出)。

B: 制冷效果取决于散热环境, 请保持通风。

C: 可选择6厘米10厘米15厘米高低脚。



Item 名称	1.2m direct cooling upright refrigerator
Model 型号	SREP-120/SFEP-120
Dimension 外形尺寸	1200*760*2000
Voltage 电源	220V/50Hz
Power 额定功率	410/650W
Temperature Range 温度	-6℃~+15/-15~-20℃
Cooling Type 制冷方式	Direct cooling 直冷
Capacity 容积	928L
Material 材质	Interior内胆: 201 Cabinet箱体: 201
Refrigerant Type 制冷剂类型	R134a/R404a
Refrigerant Throttling Mode 制冷剂节流方式	Capillary 毛细管
Keep Temp Material 保温材料	Cyclopentane 环戊烷
Defrost Water 化霜水	Enclosed unit 全封闭式
Compressor Type 压缩机类型	Forced air cooling 强制风冷
Condensing System 冷凝器类型	Evaporating Fan 蒸发风机
Temperature Controller 温控	Pc board 电脑板
Defrost Time 除霜时间	Every four hour 每隔4小时一次
Compressor work temp 压缩机启动温度	4℃
Compressor protection type 压缩机保护方式	High temperature protection 高压保护
Wattage safety type 电源保护方式	voltage changer /transommon 变压器
Heat Dissipation Type 散热方式	Front Air inlet / venting refrigeration system 前吸排风
Shelves 层架	Six layers shelves 六层
Light 灯光	According to the order 按照订单
Condensing Unit 机组	Self-Contained 一体机
Electrical Protection 电源保护方式	6.3a Fuse Wire 6.3a 保险丝
Insulation Layer Thickness 保温层厚度	Cabinet 65mm 箱体65mm; Door 55mm 门55mm
Using Temp 使用温度	1~-43℃
Packing Size 包装尺寸	/
N.W./G.W./净重/毛重	/

Approved by European CE and CB
 已通过CE、CB认证。

HISAKAGE®

1.2m direct cooling upright refrigerator 1.2米直立式冰箱

SREP-120/SFEP-120

视图方向
View Orientation

Over Look View
俯视图

Rear View
后视图

Front View
正视图

Side View
侧视图

REV
A