

# IM-240DPE-23

# Cuber, Modular & Stackable

Production Capacity (kg/24h) approx. (AT 10°C, WT 10°C): 180



PRODUCT SERIES: IM CUBE ITEM NUMBER: M120-D002 COUNTRY OF ORIGIN: UK

Hoshizaki IM-240DPE-23 Cube model is a modular and stackable ice maker producing up to 180 kg of cube ice per 24 hours. This model is compatible with Hoshizaki storage bins.

Ice cube dimensions and weight - disclaimer: The drawing is for illustration purposes only. Cube size and weight may differ due to local installation conditions.

- Ice making system with an automatic rinse cycle.
- Each ice cycle is made with fresh water.
- Closed water circuit for contamination protection.
- Closed Cell System helps produce compact, hard and geometrically perfect
- Easy external access to control panel.
- System comes with a magnetic DC water pump with variable speed and that has no direct coupling, which prevents any leakage.
- UV-C sanitization function is retrofittable.
- Cleanable air filter.
- Stainless steel frame inside.
- Easily removable water pan assembly.
- A maximum of 3 units are stackable: 1 x DPE + 2 x XPE

# ICE TYPE: Medium cubes - 23







## **ACCESSORIES INCLUDED**

Scoop, installation kit, brace

# **OPTIONAL ACCESSORIES**

4HC-H water filtration, UV-C sanitization kit, compatibility kit for stacking combinations including new and previous N series ice makers.

### CORRESPONDING WATER FILTERS

4HC-H Twin Water Filter, 4HC Replacement Cartridge

# CORRESPONDING BIN(S)

B-340SA

### **CORRESPONDING TOP KITS**

TK-48 for B-340SA (optional, not required), TK-IMD2 for B-340SA

# WARRANTY PERIOD

3 Years on Parts & Labour based on country agreement

### **EXTERIOR**

Stainless steel AISI 430, Galvanized steel (Rear)

Refrigerant: R290 / Refrigerant (kg): 0.147 / CO2 equivalent (kg): 0.441

### **OPERATING CONDITIONS**

Ambient Temp.: 1-40°C, Water Supply Temp.: 5-35°C, Water Supply Pressure: 0.07-0.8MPa (0.7-8bar), Voltage Range: Rated Voltage  $\pm 6\%$ 

### **CERTIFICATIONS**

















# IM-240DPE-23









## **TECHNICAL SPECIFICATIONS**

<b>,</b>	Production Capacity (kg/24h) approx. (AT 10°C, WT 10°C)	(kg/24h) approx.	(kg/24h) approx.	,	Electrical Circuit Breaker Protection (A)	Consumption (kW)	Water Consumption (m3/24h) approx. (AT 10°C WT 10°C)	32°C, WT 21°C)
Air Cooled	180	175	155	1/220 - 240V/50Hz	5	0.87	0.73	2.25

### SHIPPING SPECIFICATIONS

Dimensions W x D x H (mm)	Net Weight (kg)	Dimensions, Packed, W x D x H (mm)	Gross Weight, Packed (kg)	Volume Packed (m3)	
1084 x 700 x 500	75	1196 x 825 x 640	87	0.631	

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.



Hoshizaki Belgium Hoshizaki Danmark Hoshizaki Deutschland Hoshizaki France Hoshizaki Iberia Hoshizaki Italia Hoshizaki Middle East info@hoshizaki.be
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands Hoshizaki Norge Hoshizaki Sverige Hoshizaki UK Export countries Other countries info@hoshizaki.nl
salg@hoshizaki.no
orderSE@hoshizaki.dk
uksales@hoshizaki.uk
sales.ex@hoshizaki.europe.com
sales.ex@hoshizaki.europe.com

www.hoshizaki-europe.com