



TM35C

Minibar Cooler

Product Features

- Low energy consumption
- Compressor operated cooling system
- Low noise operation
- Timing function for maximum guest comfort
- SLEEP-mode function for silence period
- FAST-cool function for immediate cooling
- Adjustable shelves, also in door
- Reversible solid door
- LED interior light
- Integrated handle
- Lock

Minibar cooler with an exceptional low energy consump

This compressor operated minibar with a solid door is an excellent choice for hotels in warmer surroundings. The cooling system helps secure a lower temperature level as well as a shorter pull-down time compared to absorption operated minibars. It also has some cool programming features. It can be timed, so the compressor only runs when the room is highly likely to be empty, e.g. from 9-12 am and 6-9 pm. This means it is completely silent at other times, when guests are likely in the room. A so-called water-pack maintains the cold temperature in the minibar, when it is running. It also features a SLEEP-mode for forced silence as well as a FAST-cool function for immediate cooling. This is very handy if guests arrive at an odd hour.

Measures and Content

Temperature Range	°C	+5 to +10
Climate Class		4
Gross / Net Weight	kg	20.5 / 19.5
Gross Volume	l	27
Gross / Net Volume	l	27 / 24

Design and Material

Door No & Type	1 hinged solid door
Door Reversible	Yes
Shelves No & Type	1 plastic shelf
Feet / Legs	Adjustable feet
Exterior Finish	Black
Interior Finish	White
Interior Light	LED
Lock	Yes

Cooling and Functions


Type of Controller	Electronic
Type of Cooling	Static
Type of Defrost	Automatic
Refrigerant	R600a
Refrigerant Charge	g24
Thermometer	No

Power and Consumption

Energy Class		D
Max Ambient		30°C at 55% RH
Energy Consumption	kWh/24h	0.15
Annual Energy Cons.	kWh/year	55
Power Supply		13 Amp
Input Power	W	65
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	38

Dimensions

Internal Dimension (WxDxH)	mm	310 x 207 x 397
External Dimension (WxDxH)	mm	402 x 440 x 510
Packed Dimension (WxDxH)	mm	450 x 475 x 550
40ft Container Load	pcs	375



Display with a button for each feature



Integrated handle