

POWERFUL SEALING SOLUTION BATTERY POWERED FRICTION WELD TOOL



Eedindinije

FEATURES

- Latest brushless motor technology provides extreme long service life.
- Light weight, low cost friction weld sealer for PP & PET straps.
- No metal seals required. Co-work with any tensioners and save metal seals & time further by 15%.
- Co-work with one or several manual tensioners at a time for fast and economic sealing jobs.
- Perform multiple sealing joints and maximize products transportation security.
- Strong friction weld seals and multiple sealing joints make it a perfect tool for any fiber baling industries (e.g. cotton and coconut fiber baling etc.).
- Connect two different strap rolls to save strap feeding time and sustain non-stopping operation.
- Connect pieces of shorter straps for re-use and cost savings.
- Include a 14.4V 3000mAh NiMH or Li-Ion high capacity rechargeable battery.
- Include a BOSCH 30 minutes charger.
- Flashing light and beep sound indicate completion of sealing joints.

CDECIE	FICATION
SFLUII	TOATION

SPECIFICATION							
Model No.	Applicable	Max.		Max.		Sealing	Dimension
	Poly Straps	Strap Width		Strap Thickness		Efficiency	& Weight
						>85%	345x87x143 mm
ZP21-9D	PP & PET	19mm 3/4'	3/4"	1.53mm	0.06"	or,100%	Tool weight
						by multiple	1.6kgs/3.50Lbs
						sealing	Battery weight
						joints*1	0.92kgs/2.02Lbs

- Sealing time adjustment range: 0.6-4.8 seconds.
- Full charged battery supports up to approximately 640*2 seals per charge.
- Bosch charger voltage 100V, 115V, 230V, 240V are available for selection.
- Li-Ion battery and Li-Ion Bosch Charger are optional to replace NiMH battery and charger.

Remarks

- *1. Sealing efficiency varies based on straps' specifications, quality, sealing time set and battery capacity.
- *2. Based on PP 15 mm x 0.80mm, 1.2 sec. sealing time. Number of seals varies based on straps' specifications, quality and sealing time set.

DISTRIBUTOR



*© 2014 Pantech International Inc. All rights reserved. Worldwide Patented.

Printed in Taiwan, R.O.C.

ZAPAK is a registered trademark of Pantech International Inc.

Product and specifications subject to change without notice.

One Year limited manufacturer warranty.